



Specification

Thermal efficiency	
U _w *: Coefficient value for reference design	0,77 W/m ² K
U factor*:	0,14* Btu/h·ft ² ·F
*:	Glass 4/18/4/18/4. gas: argon, warm edge spacer, window size 48 7/16in x 58 4/16in (1230mm x 1480mm)
Profile	
Profile name:	DPQ-82
Installation depth:	82 mm
Number of chambers:	7
Thermal break:	none
Number of seals:	3
Glass	
Glazing package:	4/18/4/18/4
U _g value:	0,5 W/m ² K
Glazing Package Thickness:	48 mm

Sound insulation of available glazing:	---
Fittings	
Type:	---
Hinges:	surface
Anti-theft protection:	2 Anti-theft catches
Microventilation:	yes
Other:	---
Handle	
Colors:	---
Handle model:	1006
Dimensions	
Maximum window width - single sash:	1500 mm
Maximum window height - single sash:	2575 mm
Maximum window width - double sash with a movable post:	2085 mm
Maximum window height - double sash with a movable post:	2480 mm
Maximum sash area:	2,25 m ²
Maximum size of fixed glazing (when using a special glass, Maximum area of 7m2 and weight of 250 kg):	3500 x 2900 mm lub 2900 x 3500 mm

Photos

