

DA-77 HST



Specification

| Thermal efficiency | |
|---|---|
| U _w *: Coefficient value for reference design | 1,1 W/m ² K |
| U factor*: | --- |
| *: | --- |
| Profile | |
| Profile name: | DA-77 |
| Installation depth: | Sash: 77 mm Frame: 174 mm |
| Number of chambers: | 3 |
| Thermal break: | 35 mm glass-fibre reinforced polyamide thermal breaks |
| Number of seals: | Two EPDM dual-component synthetic rubber seals |
| Glass | |
| Glazing package: | Triple glazing package 4x18x4x18x4 |
| U _g value: | 0,5 W/m ² K |
| Glazing Package Thickness: | glazing thickness available: from 14 to 58 mm |
| Sound insulation of available glazing: | w: from 31 to 47 dB |
| Fittings | |
| Type: | Lift - sliding fitting |

| | |
|--|---|
| Hinges: | n/a |
| Anti-theft protection: | n/a |
| Microventilation: | yes |
| Other: | n/a |
| Handle | |
| Colors: | --- |
| Handle model: | Made of aluminum |
| Maximum construction dimensions | |
| Width: | 6500 mm |
| Height: | 3000 mm |
| Sash size | |
| Min. sash width: | 900 mm |
| Max. sash width: | 3300 mm |
| Min. sash height: | 1900 mm |
| Max. sash height: | 3200 mm |
| Max. sash weight: | 300 kg |
| Max. sash area: | --- |
| Other | |
| Other: | OPTION: Automatic doors - opening and closing with remote control |

Photos

